


UP-NT6226GK-EAE00



ENGINEERING CODE
603BAS6C4FI



REFRIGERANT
R-449A



POWER SUPPLY
220-240 V 50 Hz



APPLICATION
HBP



MOTOR TYPE
CSR



STANDARD
EN13215_RG20



COOLING CAPACITY
1832 W



EFFICIENCY
1.93 W/W

CE

ECODESIGN COMPLIANT

Performance Data Sheet according to EU Regulation 2015/1095

PERFORMANCE CURVE

Parameters at full load and ambient temperature 25 °C

| Evaporating Temperature °C | Cooling Capacity W | Power Consumption W | Efficiency W/W |
|----------------------------|--------------------|---------------------|----------------|
| -10 | 2013 | 900.8 | 2.23 |

PERFORMANCE CURVE

Parameters at full load and ambient temperature 32 °C

| Evaporating Temperature °C | Cooling Capacity W | Power Consumption W | Efficiency W/W |
|----------------------------|--------------------|---------------------|----------------|
| -10 | 1832 | 951.6 | 1.93 |

PERFORMANCE CURVE

Parameters at full load and ambient temperature 43 °C

| Evaporating Temperature °C | Cooling Capacity W | Power Consumption W | Efficiency W/W |
|----------------------------|--------------------|---------------------|----------------|
| -10 | 1531 | 1027.5 | 1.49 |