



TECHNICAL DATASHEET

GALAXY® 4828



Tube- CR Barrier- PA Friction- NBR Reinforcement- PET Friction-SBR Cover- CIIR

- ♦ Two Spiral Barrier Hose
- ♦ J51 AI Outside Diameters
- ♦ Temperature Range -22°F to 257°F (-30°C / +125°C)
- ♦ Compatible with:
 - R12 / R134a Refrigerants
 - Mineral oils / PAG's
- ♦ Meets J2064 "Type C Class II" Hose Performance
- ♦ Flexible, easy to route

| DASH | SIZE | | INSIDE DIAMETER | | | | OUTSIDE DIAMETER | | | | WEIGHT | |
|------|-------|----|-----------------|-------|------|------|------------------|-------|------|------|--------|------|
| | | | INCH | | mm | | INCH | | mm | | | |
| | | | min | max | min | max | min | max | min | max | | |
| -6 | 5/16 | 8 | 0,307 | 0,337 | 7,8 | 8,6 | 0,688 | 0,750 | 17,5 | 19,1 | 0,18 | 0,27 |
| -8 | 13/32 | 10 | 0,401 | 0,436 | 10,2 | 11,1 | 0,844 | 0,906 | 21,4 | 23,0 | 0,26 | 0,39 |
| -10 | 1/2 | 12 | 0,490 | 0,535 | 12,4 | 13,6 | 0,937 | 1,000 | 23,8 | 25,4 | 0,30 | 0,45 |
| -12 | 5/8 | 16 | 0,615 | 0,660 | 15,6 | 16,8 | 1,062 | 1,124 | 27,0 | 28,5 | 0,35 | 0,52 |